

EVD-40S-P

40kW Wall DC Charger Single Gun RFID [CCS]



The Future of EV Charging

The EVD-40S-P is a three-phase, commercial DC charging unit, featuring a single CCS gun.

With it's high power, it's an ideal small-scale commercial charging unit that is also compatible with our bespoke app, allowing for easy fleet and cost management - as well as being able to manage load balancing for larger scale charging across multiple vehicles.

The RFID unit comes with one RFID card as standard, with additional RFID cards (EV-RFID) available for purchase. Optional floor stands (EV-FLRSTAND-40KW) & optional ground mounts (EV-GM40KW-2) are available to purchase.



CCS
CONNECTOR



ULTRA RAPID
CHARGING



CONTACTLESS
PAYMENTS¹



RFID
CONTROL



OCPP
COMPLIANT²



5 YEAR / 30,000 HOUR
WARRANTY

¹ Compatible to upgrade with contactless payment terminal. ² Compliant with multiple back-office solutions.

METHODS OF CONTROL

Plug & Charge - Project EV's ethos is to make charging electric vehicles easy and stress free for all. With the Plug and Play mode you do not require any additional software or applications to control your EV charge point, you simply plug your car into a Project EV device, and the charge begins.

RFID - RFID Mode Charging is an easy simple way for users to control their EV Charge Point with a swipe of a card. One RFID card is supplied as standard, however extra cards can be supplied for those interested in public charging.

Project EV App - The FREE Project EV App allows you to choose and customise charging rates, prioritise off-peak charging to maximise savings and create charging records; so you can see and control all your data.

Project EV Pro App - The Project EV Pro App is a unique EV charging platform, providing you the ability to utilise public charging capabilities and manage and control multiple chargers - from which you can generate a fluid revenue stream.



Input & Output

Input Amps	64A AC
Input voltage	320~457V AC
Input frequency	50HZ
DC outlet type	CCS
Output voltage	CCS:DC 150~1000V DC
Max. output power	40KW
Max. output current	100A DC
Voltage accuracy	$\leq \pm 0.5\%$
Current accuracy	$\leq \pm 1\%$
Ripple coefficient	RMS: $\pm 0.5\%$; Peak: $\leq \pm 1\%$
Meeting accuracy	0.5%
Efficiency	$\geq 94\%$
Cable Length	5m

Protection

Over voltage protection	✓
Under voltage protection	✓
Over load protection	✓
Over-temp protection	✓
Emergency protection	✓
Lightning protection	✓

Function & Accessory

Display	7 inch touch screen
Ethernet/WIFI/4G	Yes/Yes/Opt
Charging mode	APP/RFID (opt)/ Plug and Charge
Ocpp	1.6J3ON
LED Indicator light	✓

Working Environment

Protection degree	IP54
Environment temperature	-25°C~+50°C
Relative humidity	5%-95% non-condensing
Cooling	Forced air cooling
Standby power consumption	<30W
Noise emission	$\leq 65\text{db}$

Mechanical

Dimension (W/H/D)	632/858/300mm
Weight	84KG

Certification

CE	✓
----	---

Mounting & Accessories

Wall-mounting	Standard
Floor-pole	Opt. EV-FLRSTAND-40KW
Grout-mounting	Opt. EV-GM40KW-2
Dynamic Load Management	Opt. EV-TPM-200A

